General Information

Cutting mills are suitable for the grinding of soft, medium-hard, elastic, fibrous, and heterogeneous mixes of products. The SM 100 is the budget-priced basic model among the RETSCH cutting mills. With its strong 1.5 kW drive and 1,500 rpm rotor speed the mill is particularly suitable for routine applications. Cleaning is made particularly easy. In combination with the wide choice of bottom sieves, hoppers and collecting vessels, the mill can be easily adapted to varying application requirements. The SM 100 can be bench-mounted; alternatively a convenient base frame on wheels is available.

Application Examples

animal feed, bones, cardboard, drugs, electronic scrap, food, leather, lignite, paper, plant materials, plastics, resins, rubber, spices, straw, textiles, wood, ...

Product Advantages

- optimum cutting effects
- quick and easy cleaning due to smooth surfaces and push-fit rotor
- for routine applications
- defined final fineness due to bottom sieves with aperture sizes from 0.25
 20 mm
- feed size
- wide range of accessories including various hoppers, collection systems, rotors and sieves

carbide


• highest safety standards

Features

Applications Field of application


Feed material Size reduction principle Material feed size* Final fineness* Speed at 50 Hz (60 Hz) Rotor peripheral speed Rotor diameter Types of rotors Types of hoppers Material of grinding tools

size reduction by cutting agriculture, biology, chemistry / plastics, engineering / electronics, environment / recycling, food, medicine / pharmaceuticals soft, medium-hard, elastic, fibrous shearing, cutting < 60 x 80 mm 0.25 - 20 mm 1.500 min⁻¹ 9.4 - 11.4 m/s 129.5 mm parallel section rotor / 6-disc rotor standard, long stock stainless steel, steel for heavy-metal free grinding, tungsten













Subject to technical modifications and errors



Sieve sizes	trapezoid holes 0.25 / 0.50 / 0.75 / 1.00 / 1.50 mm square holes 2.00 / 4.00 / 6.00 / 8.00 / 10.00 / 20.00 mm	
Collector systems / capacities	collecting receptacle 5 I / optional: 30 I collecting unit 0.25 / 0.5 I	
Drive	3-phase motor	
Drive power	1,5 kW	
Electrical supply data	different voltages	
Power connection	3-phase	
Protection code	IP 54	
W x H x D closed	582 x 1675 x 700 mm (with base frame and standard hopper)	
Net weight	~ 73 kg without hopper, rotor and base frame	
Documentation	Operation & Application Video	
Standards	CE	
*depending on feed material and instrument configuration/settings		



Videolink



http://www.retsch.com/sm100

Function Principle

Size reduction in the Cutting Mill SM 100 takes place by cutting and shearing forces. The sample comes into contact with the rotor, and is comminuted between the blades and the stationary standard cutting bars inserted in the housing.

In the 6-disc rotor, spirally arranged reversible hard metal plates operate by cutting in sequence.

The knives of the parallel section rotor carry out comminution with a powerful cutting action.

The dwelling time of the sample in the chamber is short; as soon as it is small enough to pass through the openings of the bottom sieve it is discharged and collected in the receptacle. The rotor speed of 1.500 min⁻¹ ensures gentle and rapid size reduction.

Order data

Cutting Mill SM 100

with collecting receptacle, 5 litres (please order rotor, hopper, bottom sieve and optional base frame separately) 20.727.0001 SM 100, 3~ 400 V, 50 Hz 20.727.0009 SM 100, 220-230 V, 50/60 Hz, with frequency converter for grinding without heavy-metal contamination

20.727.0002 SM 100, 3~ 400 V, 50 Hz 20.727.0010 SM 100, 220-230 V, 50/60 Hz, with frequency converter

other electrical versions available Base frame 22.824.0005

Base frame with wheels for SM 100

© Retsch GmbH - www.retsch.com - info@retsch.com Subject to technical modifications and errors page 3/5 11.06.2013



6-disc rotor, stainless steel, with reversible cutting

Cutting Mill SM 100

Accessories SM 100 / SM 200 / SM 300

Rotors

22.608.0022

	tips of tungsten carbide	
22.608.0021	Parallel section rotor, stainless steel	
Rotors for grinding without heavy-metal contamination		
22.608.0028	6-disc rotor, steel 1.0580, with reversible cutting tips of tungsten carbide	
22.608.0018	Parallel section rotor, steel 1.0580	
Hoppers		
22.785.0007	Universal hopper with plastic plunger, for SM 100	
22.408.0004	Long stock hopper with wooden plunger, for SM 100	
Additional plungers for universal hopper		

22.725.0010Plastic plunger22.725.0011Wooden plunger22.725.0012Aluminum plunger

Bottom sieves of stainless steel

Trapezoid holes, 0.25 mm
Trapezoid holes, 0.50 mm
Trapezoid holes, 0.75 mm
Trapezoid holes, 1.00 mm
Trapezoid holes, 1.50 mm
Square holes, 2.00 mm
Square holes, 4.00 mm
Square holes, 6.00 mm
Square holes, 8.00 mm
Square holes, 10.00 mm
Square holes, 20.00 mm

Bottom sieves of steel 1.0353 for grinding without heavy-metal contamination

03.647.0326	Trapezoid holes, 0.50 mm
03.647.0327	Trapezoid holes, 0.75 mm
03.647.0328	Trapezoid holes, 1.00 mm
03.647.0333	Square holes, 4.00 mm
03.647.0335	Square holes, 8.00 mm
03.647.0359	Square holes, 10.00 mm

Collecting receptacles

22.003.0008 22.523.0001 Collecting unit 250 / 500 ml, incl. 2 sample bottles Sample bottles, 250 ml, 10 pieces

© Retsch GmbH - www.retsch.com - info@retsch.com Subject to technical modifications and errors page 4/5 11.06.2013



22.003.0007	Collecting receptacle, 5 litres, stainless steel
22.003.0010	Collecting receptacle, 30 litres, plastic, incl. adapter and filter hose
22.187.0006	Ring-type filter for collecting receptacle 5 litres
22.748.0001	Dust filter clamping rings for ring-type filter, incl. 5 dust filters
22.524.0002	Dust filters for ring-type filter, 25 pieces
22.187.0007	Filter hose for collecting receptacle 5 litres, incl. holder
Accessories for Rotors	
22.908.0001	Reversible cutting tips, tungsten carbide, for 6-disc rotor, 10 pieces
22.151.0004	Cutting plates, stainless steel, for parallel section rotor, 1 set (3 pieces)
22.151.0006	Cutting plates, steel 1.1740, for parallel section rotor, 1 set (3 pieces), for grinding without heavy-metal contamination
Stationary cutting bars	
22.152.0007	Cutting bars, stainless steel,, 1 set (3 pieces), for SM 100
22.152.0009	Cutting bars, steel 1.1740,, 1 set (3 pieces), for SM 100
Additional items	
22.225.0002	Replacement extraction tool for rotor