

Sample Splitters RT 6.5 - RT 75

General Information

A faultless and comparable analysis is closely linked to an accurate sample handling. Only a sample representative of the initial material can provide meaningful analysis results. Sample splitters ensure the representativeness of a sample and thus the reproducibility of the analysis.

The sample splitters RT are ideal for the on-site reduction of sample material. They are easy to use, easy to clean and do not need an electrical power supply.



Application Examples

cement clinker, chemicals, coffee, construction materials, fertilizers, fillers, flours, grains, metals powders, minerals, nuts, sand, seeds, soils, washing powder, ...

Product Advantages

- for use in laboratory and on-site
- high-precision manual dividing process
- dividing process according to DIN 51701

Features

Applications	sampling and sample dividing
Field of application	agriculture, biology, chemistry / plastics, construction materials, engineering / electronics, environment / recycling, food, geology / metallurgy, glass / ceramics, medicine / pharmaceuticals
Feed material	bulk materials
Material feed size*	RT 6.5: ~ 4 mm RT 12.5: ~ 8 mm RT 25: ~ 16 mm RT 37.5: ~ 25 mm RT 50: ~ 33 mm RT 75: ~ 50 mm
Batch size / feed quantity*	RT 6.5: <= 3 RT 12.5: <= 3 RT 25: <= 16 RT 37.5: <= 16 RT 50: <= 16 RT 75: <= 16
Number of divisions	2
W x H x D	RT 6.5: 300 x 270 x 250 mm RT 12.5: 300 x 270 x 250 mm RT 25: 620 x 420 x 260 mm RT 37.5: 620 x 420 x 260 mm RT 50: 620 x 420 x 260 mm RT 75: 620 x 420 x 260 mm
Net weight	RT 6.5: ~ 3.5 kg RT 12.5: ~ 3.5 kg RT 25: ~ 21.5 kg RT 37.5: ~ 21.5 kg RT 50: ~ 21.5 kg RT 75: ~ 21.5 kg

Sample Splitters RT 6.5 - RT 75

*depending on feed material and instrument configuration/settings

Sample Splitters RT 6.5 - RT 75

Videolink



<http://www.retsch.com/rt>

Function Principle

With sample splitters, one of the receptacles is used to pour a well mixed sample evenly into the dividing head. The material runs through the alternately arranged passages in the opposite direction into the two collecting receptacles under the dividing head outlets. With every operation the feed sample is halved. This can be repeated as many times as necessary until the required dividing quantity has been obtained. □

Order data

Sample Splitter RT 6.5 and RT 12.5

incl. 3 collecting receptacles 1.5 litres each of tin plate, stand of coated sheet steel and dividing head made of stainless steel

40.610.0001	Sample Splitter RT 6.5, with 12 slots, 6.3 mm
40.610.0002	Sample Splitter RT 12.5, with 18 slots, 12.5 mm
05.000.0019	Spare collecting receptacle 1.5 litres (for RT 6.5 and RT 12.5), 1 piece

Sample Splitter RT 25, RT 37.5, RT 50 and RT 75

incl. 3 collecting receptacles 8 litres each, stand and dividing head, all made of galvanized sheet

40.610.0003	Sample Splitter RT 25, with 16 slots, 25.0 mm
40.610.0004	Sample Splitter RT 37.5, with 12 slots, 37.5 mm
40.610.0005	Sample Splitter RT 50, with 8 slots, 50.0 mm
40.610.0006	Sample Splitter RT 75, with 6 slots, 75.0 mm
42.147.0002	Spare collecting receptacle 8 litres (for RT 25, RT 37.5, RT 50 and RT 75), 1 piece